

# SM-4000

## Personal Silica Monitor Complements Compliance Air Sampling



- Low sensing range down to  $1 \mu\text{g}/\text{m}^3$
- High precision of  $\pm 3 \mu\text{g}/\text{m}^3$
- Readings display in  $\mu\text{g}/\text{m}^3$  – no conversions needed
- Comes standard with GS-3 Cyclone that conforms to ISO 7708/CEN criteria
- Concurrent filter sampling option for lab analysis and/or cross-calibration of displayed results
  - Gravimetric filter cassette located directly behind the sensor for maximum particle deposition
  - Internal pump flows at 2.75 L/min (user adjustable)
- Sensor and filter cassette clips directly in the breathing zone
- Datalogging
  - DustComm Software for downloading, basic trend analysis, and graphical analysis and comprehensive graphical reporting

Silica Monitor SM-4000 is a direct-reading personal dust monitor optimized for the measurement of silica levels specified in the OSHA Final Silica Rule. Calibrated to a known amount of silica dust, SM-4000 provides direct readings for determination of peak silica concentrations for mitigation and lower TWAs. The SM-4000 internal pump and gravimetric filter cassette (directly behind the sensor) provide for concurrent collection of a gravimetric sample for silica analysis and cross-calibration. Use the SM-4000 for:

- Perimeter monitoring of regulated areas with user-set alarms
- Evaluation of controls and worker activities
- Recording time history of dust levels
- Filter sampling for lab analysis
- Task monitoring
- Selecting PPE



# SM-4000 Personal Silica Monitor

Complementary Monitoring for Silica Mitigation

## Easy to Use SM-4000



Clip the sensor with GS-3 Cyclone to a worker's collar in the breathing zone.



Clip the SM-4000 to a worker's belt.



Read dust concentration on the SM-4000 display. Download data for graphing/reporting.

## Performance Profile

**Sensor:** Light scattering

**Flow Rate:** 2.75 L/min (user adjustable)

**Sensing Range:** 1 to 20,000  $\mu\text{g}/\text{m}^3$  (0.001 to 20  $\text{mg}/\text{m}^3$ )


**Precision:**  $\pm 3 \mu\text{g}/\text{m}^3$  (0.003  $\text{mg}/\text{m}^3$ )

**Display:** Concentration in  $\mu\text{g}/\text{m}^3$ , TWA, STEL, MIN, and MAX

**Accuracy:**  $\pm 10\%$  to filter gravimetric SAE fine test dust

**Gravimetric Filter Sampling Requirements:** 37-mm PVC filter for the supplied 37-mm in-line cassette (25-mm filter and cassette options are available)

## Ordering Information

Description	Cat. No.
<b>SM-4000 Personal Silica Monitor Kit</b> includes SM-4000 Monitor, GS-3 respirable cyclone, 37-mm in-line filter cassette, serial computer cable, serial to USB adapter cable, battery charger, zeroing filter, HAZ-DUST media CD with instruction manual and DustComm Pro Software (compatible with Windows XP, 7, 8, and 10), and carry case 	<b>110-240 V</b> 770-700

 Requires calibration with equipment sold separately; see below

Accessories	Cat. No.
<b>Calibration Standard for Monitor</b> , for verifying span and optical sensor performance	770-710
<b>Calibration Jar</b> , for calibrating and setting pump flow when using a respirable cyclone	225-112
<b>Cleaning Kit</b> , for cleaning SM-4000 Monitor	770-305
<b>Replacement Battery Pack</b>	770-4105

### SKC Limited Warranty and Return Policy

SKC products are subject to the SKC Limited Warranty and Return Policy, which provides SKC's sole liability and the buyer's exclusive remedy. To view the complete SKC Limited Warranty and Return Policy, go to <http://www.skcinc.com/warranty>.

