

From **SKC**, a trusted leader in industrial hygiene instrumentation...

# NoiseCHEK

PERSONAL DOSIMETER

- ▶ **Intuitive**
- ▶ **Largest display screen on a cable-free dosimeter**
- ▶ **1/3 octave band filter standard on all models**
- ▶ **Reliable 1/2-inch microphone — no adapter needed**
  - Auto calibration with AcoustiCHEK Calibrator
- ▶ **Bluetooth® models feature**
  - Connectivity to SmartWave dB mobile app
  - Voice tag recording
  - Threshold-triggered noise event recording
  - Field note creation
- ▶ **Small and tough for easy worker acceptance**
- ▶ **Designed, built, sold, supported, and serviced by SKC — a name you have trusted for over 55 years**
- ▶ **Made in the USA**
- ▶ **Expert support from the SKC team of Certified Occupational Hearing Conservationists (COHC)**
  - On-site seminars are available to help you with noise monitoring training



Straight-forward Noise Measurement that  
**MAKES YOUR JOB EASIER!**

## Connect with NoiseCHEK from Mobile and PC

### SmartWave dB app

Free for iOS and Android Tablets/Phones

- Start/pause/stop NoiseCHEK
- View setup and monitor readings for up to four virtual dosimeters
- View octave band levels and history
- Add and review field notes on history files
- Generate and share compliance reports via e-mail and text

### DataTrac dB Software

Free Download to PC

- Set up four virtual dosimeters
- Schedule sampling
- Download data
- Enable/disable device lockout
- Listen to voice recordings
- Review notes
- Generate and share compliance reports

## PERFORMANCE PROFILE

- **Measuring Range:** 70 to 140 dB and Peak level up to 143 dB
- **Weighting:** A, C, and Z; Peak C or Z weighted
- **Response Time:** Fast and slow
- **Exchange Rate:** Selectable from 3, 4, or 5 dB
- **Virtual Dosimeters:** Program up to 4 for simultaneous monitoring including OSHA HC, OSHA PEL, MSHA, ACGIH, or custom
- **Display:** TFT monochrome, front lit 1.8 inches (45.72 mm), 9 lines display user-selectable data for each virtual dosimeter including: SPL, Lavg, Leq, Dose, Peak, TWA, projected dose and TWA, and exposure
- **Standards:** Meets ANSI S1.25, IEC61252 (Class 2)
- **Datalogging/Time History:** 180+ hours memory capacity (selectable 1, 30, and 60-second sampling rate)
- **Connectivity:** Bluetooth low energy (BLE) to mobile device with app; USB to PC with app
- **Run Time:** 40+ hours
- **Power:** Li-Ion polymer rechargeable battery, 3.7 V, 1200 mAh
- **Dimensions:** 3.9 x 1.9 x 2 inches (99 x 48 x 51 mm)
- **Weight:** 4.1 oz (117 gm)

We are proud to introduce the SKC NoiseCHEK Dosimeter! SKC's team of Certified Occupational Hearing Conservationists designed NoiseCHEK specifically for accuracy and your easy daily use. NoiseCHEK provides more data and versatility than any Class 2 dosimeter on the market. From setup to monitoring and accessing logged data, NoiseCHEK takes the complexity out of noise measurement. NoiseCHEK is available directly from SKC, which means you experience the high level of SKC quality, service, and expertise that you have always trusted.

[www.skcinc.com](http://www.skcinc.com) | 800-752-8472



## ORDERING

NoiseCHEK	Cat. No.	Price
<b>Single Kit</b> includes dosimeter, 1-unit charging dock with power supply, USB cable, and USB drive with manual, in a protective carry case	701-001K	Call SKC.
<b>Single Kit with Class 2 Calibrator</b> includes dosimeter, one-unit charging dock with power supply, AcoustiCHEK Calibrator, USB cable, and USB drive with instruction manual, in a protective carry case	701-001K-C	Call SKC.
<b>3-pack Kit with Class 2 Calibrator</b> includes 3 each: dosimeters and one-unit charging docks with power supplies; 1 each: AcoustiCHEK Calibrator, replacement windscreen, USB cable, and USB drive with manual, in a protective carry case	701-001K3-C	Call SKC.
<b>5-pack Kit with Class 2 Calibrator</b> includes 5 dosimeters, five-unit charging dock with power supply, AcoustiCHEK Calibrator, replacement windscreen, USB cable, and USB drive with manual, in a protective carry case	701-001K5-C	Call SKC.

☒ Requires calibration using AcoustiCHEK calibrator sold separately; see Accessories

Accessories	Cat. No.	Price
<b>1-unit Charging Dock</b> provides charging and connection to PC, requires power supply; see below	701-002	Call SKC.
<b>5-unit Charging Dock</b> provides charging and connection to PC, requires power supply; see below	701-003	Call SKC.
<b>Power Supply for Charging Docks, 12 V DC, with interchangeable plugs</b>	100-240V	220-600
<b>Replacement Windscreen</b>	701-004	Call SKC.
<b>Replacement Microphone, 1/2 inch</b>	701-005	Call SKC.
<b>AcoustiCHEK Calibrator, Class 2, for 1/2-inch microphones, includes AA batteries and Certificate of Manufacturer Calibration</b>	703-002	Call SKC.

More NoiseCHEK Kits and non-BLE model are available. Contact SKC for more information.

[www.skcinc.com](http://www.skcinc.com)