
AirLite Sample Pump

Economical Abatement Pump!

Flows: 5 to 3000 ml/min







4.6 inches

 Patented* flow control system holds constant flow to ± 5% of set-point

- 1000 to 3000 ml/min flow range
- Low flows from 5 to 500 ml/min with All-in-One adjustable tube holder

• Alkaline battery powered — no charging!

- Economical, disposable AA alkaline batteries
- Ready to go anytime!
- Ideal for abatement, indoor air sampling, and emergency response in non-hazardous locations

Easy operation

- Turn it on, calibrate, and sample
- Easy access battery compartment

Over 10 hours run time

• AirLite® fits in the palm of your hand!

- Only 12 ounces (340 grams)
- 4.6 x 3 x 1.75 inches (11.7 x 7.6 x 4.4 cm)

Features maintain sample integrity

- Constant flows up to 3000 ml/min
- Compensates up to 20 inches water back pressure at 2 L/min
- Compensates for temperature changes from 41 to 122 F (5 to 50 C)
- Low battery and flow fault shut-off and indicator
- Rugged RFI/EMI-shielded case, CE marked
- New model with timer!

Ordering Information

AirLite requires 1/4-inch ID tubina.

Cat. No.	Cat. No.
(without timer)	(with timer)
110-100*	110-100-T
110-100K5	110-100-TK5
110-100K5D	110-100-TK5D
225-1	
210-500	
224-902	
	(without timer) 110-100* 110-100K5 110-100K5D 225-1 210-500

^{*} U.S. Patent No. 6,741,056

